

DAX DRM-2324

2U Rack Mount Appliance for up to 24 Port Solutions



Chassis

- » 2U rack mount chassis
- » Dual 460 watt hot-swap power supplies

Processor

- » 2.8 GHz Pentium 4 processor (LGA775 Socket)

Chipset

- » Intel® "Mukilteo" E7230 MCH + ICH7R chipset
- » Support for 1066MHz (1.066GHz) FSB
- » SMSC SCH5017 Super I/O chip

Memory

- » 1 GB DDR2 memory
- » Dual channel memory bus
- » Up to 8GB unbuffered ECC DDR2-533/667 memory

Expansion Slots

- » Two full length PCI 32-bit, 33MHz slots
- » One half length PCI 32-bit, 33MHz slots

Mass Storage

- » Two 160 GB SATA II (3GB) Mirrored hard drives (7200 RPM)
- » Three hot swap carriers (for hard drives) Two used, One free for expansion
- » One 5.25" DVD-ROM device
- » One 3.5" floppy

Integrated Rear Panel I/O

- » One 9-pin 16550 UART serial port
- » One ECP/EPP/SPP parallel port (via header) which will reduce the total available PCI slots to two
- » One 15-pin VGA port
- » Four USB 2.0 ports
- » Stacked PS/2 mouse and keyboard connectors
- » Two RJ-45 10/100/1000 LAN ports

Integrated Front Panel I/O

- » Power Switch
- » Reset Switch
- » Two USB ports
- » HDD, LAN, PWR indicators
- » One 5.25" mass storage expansion slot

Physical Specifications

- » 19" W x 27" D x 3.5" H
- » Temperature: 0° C (32° F) ~ 50° (122° F)
- » Humidity: 5% - 95% non-condensing

Operating System

- » Windows XP Pro
- » Windows 2003 SERVER

DAX Systems, Inc.
343 New Road, Unit 4
Parsippany, NJ 07054

877.432.9797 toll free
973.227.8111 main
973.227.8197 fax

daxsystems.com