



## DRM-28027X 2U High Performance Server

System Features	
Operating System:	Windows Server 2003, Windows XP, Linux
Processors Available:	Dual INTEL 64-bit XEON Quad-Core or Dual-Core with 667/1066/1333 MHz FSB
Chipset:	Intel® 5000P (Blackford) Chipset
Front Side Bus:	(FSB 667 / 1066 / 1333)
M/B Form Factor:	Extended ATX - 12.0" width x 13" length , (30.5cm x 33.2 cm)
Memory	
Memory:	Up to 32 GB FB, ECC DDR2 667/533 SDRAM
Storage	
Drive controllers:	INTEL ESB2 SATA 3 Gbps for 6 x SATA connectors
	RAID 0, 1, 5, 10 Support for Windows RAID 0, 1, 10 Support for Linux
Audio, Slots and Ports	
Ports:	2 x USB (rear)
	1 x Serial (rear)
	1 x PS/2 mouse
	1 x PS/2 keyboard
	2 x RJ-45 ( GB LAN)
	1 x external VGA monitor
Slots:	3 x PCIe (Ver. 2.2) slots
Rear Panel:	Riser Card for 3 x PCIe cards
Graphics and Input / Output devices	
Graphics card:	ATI ES1000 controller with 16 MB video memory
Input devices:	PS/2 101 Keyboard
	PS/2 2-button optical mouse

<b>Communications Features</b>	
Network:	2x Intel® (ESB2/Gilgal) 82563EB Gigabit LANs
<b>Product Specifications</b>	
Dimensions:	3.5"H x 19"W x 26"D
<b>Power</b>	
Power Supply:	Dual 500 Watt Hot Swap Power Supplies
<b>Service and Support</b>	
Warranty:	90 Day advance replacement, 3 Year return to depot warranty