

DAX DRM-4724

4U Rack Mount Chassis for up to 48 Ports



Chassis

- » 4U rack mount chassis
- » Dual 400 watt hot swap power supplies

Processors

- » 3.6 GHz Pentium 4 processor (LGA Socket 775)
- » 800 MHz front side bus

Chipset

- » Intel® 915GV chipset
- » Intel® 915GV Express chipset
- » Intel® 82801FB I/O Controller Hub (ICH6)

Memory

- » 1 GB dual channel (128-bit wide) memory interface
- » Supports Unbuffered PC3200 (DDR400) or PC2700 (DDR333) DDR SDRAM DIMM
- » Supports maximum of 4GB system memory, up to 512Mbit technology for x8 and x16 devices, non-ECC memory

Expansion Slots

- » Six PCI

Mass Storage

- » Two 320 GB SATA II (3GB) Mirrored hard drives (7200 RPM)
- » Two hot swap carriers (for hard drives)
- » One 5.25" DVD-ROM device
- » One 3.5" floppy
- » Space for one additional 3.5" internal device
- » Adaptec SATA RAID Controller

Integrated Rear Panel I/O

- » One mini-DIN-6 PS/2 mouse port
- » One mini-DIN-6 PS/2 keyboard port
- » One DB-25 parallel port
- » One DB-9 serial port
- » One DB-15 VGA port
- » One RJ45 LAN port
- » Four USB 2.0/1.1 ports
- » Mic-in, line-in and line-out

Integrated Front Panel I/O

- » Power ON/OFF switch
- » Reset switch
- » Keyboard Lock switch
- » Two USB ports
- » Power LED
- » HD LED

Physical Specifications

- » 19" W x 18" D x 7" H
- » Front door key lock to protect unauthorized access

O/S

- » Win XP Pro
- » Win 2003 SERVER
- » Linux

DAX Systems, Inc.
343 New Road, Unit 4
Parsippany, NJ 07054

877.432.9797 toll free
973.227.8111 main
973.227.8197 fax

daxsystems.com