

DAX DRM-52024

5U Rack Mount Chassis for up to 96 Ports and above



Chassis

- » 5U rack mount chassis
- » Dual 400 watt hot swap power supplies

Processors

- » Pentium 4 Single Board Computer
- » 3.6 GHz Pentium 4 processor (Socket 775)
- » 800 MHz front side bus

Chipset

- » Intel® 915GV + ICH6 chipset

Memory

- » 2 GB Memory Dual channel DDR2 400 MHZ
- » Supports up to 4 GB

On-Board LAN

- » Intel 82573L PCI Express Gigabit Ethernet x 2
- » RJ45 with LED connector x 2 (Active, Link 10, 100, and 1000 LAN LED)
- » 2-pin header for extended LAN LED x 3 (Active, Link 100, and 1000 LAN LED)
- » LAN Status LED defined:
 - 10: LED Off
 - 100: Green LED
 - 1000: Orange LED
- » Support Boot From LAN (PXE)

On-Board Video

- » Chipset Built-in integrated Graphics Device
- » Analog Display Support
- » Up to 2048 x 1536 @ 85 Hz for CRT

Expansion Slots

- » 11 full length PCI slots

Mass Storage

- » Four 320 GB SATA II hard drives (7200 RPM) RAID V configuration
- » Four hot swap carriers for hard drives
- » One DVD/RW drive
- » One Floppy
- » Two 5.25" external expansion slots

Integrated Rear Panel I/O

- » One 15-pin VGA port
- » Two Intel GBE LAN
- » One Keyboard connector
- » One Mouse connector
- » One ECP/EPP/SPP parallel port (via header)

Integrated Front Panel I/O

- » ON/OFF switch
- » Reset switch
- » Power LED
- » HDD LED

Physical Specifications

- » 19" W x 27" D x 8.75" H
- » Temperature: 0° C (32° F) ~ 50° (122° F)
- » Humidity: 5% - 95% non-condensing
- » Front door key lock to prevent unauthorized access

O/S

- » Win XP Pro
- » Win 2003 SERVER
- » Linux

DAX Systems, Inc.
343 New Road, Unit 4
Parsippany, NJ 07054

877.432.9797 toll free
973.227.8111 main
973.227.8197 fax

daxsystems.com